

A Smarter Way for Your Broadband Life

Huawei EG8242H, an intelligent bridging-type ONT

Smart service, interconnection, and O&M



Device Parameters

| | | | |
|------------------------|----------------------------------|---------------------------|----------------------------|
| Dimensions (L x W x H) | 220 mm x 160 mm x 32 mm | System power supply | 11–14 V DC, 2 A |
| Weight | About 380 g | Static power consumption | 5.5 W |
| Operating temperature | 0°C to +40°C | Maximum power consumption | 14 W |
| Operating humidity | 5% RH to 95% RH (non-condensing) | Ports | 4GE + 2POTS + CATV |
| Power adapter input | 100–240 V AC, 50/60 Hz | Indicators | POWER/PON/LOS/LAN/TEL/CATV |

Interface Parameters

| GPON Port | Ethernet Port | POTS Port |
|--|--|--|
| <ul style="list-style-type: none"> • Class B+ • Receiver sensitivity: -27dBm • Wavelengths: US 1310 nm, DS 1490 nm • Wavelength blocking filter (WBF) • Flexible mapping between GEM Port and TCONT • GPON: consistent with the SN or password authentication defined in G.984.3 • Bi-directional FEC • SR-DBA and NSR-DBA | <ul style="list-style-type: none"> • Ethernet port-based VLAN tags and tag removal • 1:1 VLAN, N:1 VLAN, or VLAN transparent transmission • QinQ VLAN • Limit on the number of learned MAC addresses • MAC address learning • Local switching/isolation based on Ethernet ports • Transparent transmission of IPv6 packets at Layer 2 | <ul style="list-style-type: none"> • Maximum REN: 4 • G.711A/μ, G.729a/b, and G.722 encoding/decoding • T.30/T.38/G.711 fax mode • DTMF • Emergency calls (with the SIP protocol) |
| | | CATV Port |
| | | <ul style="list-style-type: none"> • Bandwidth 54-870 MHz • Output resistance 75 ohms |

Product Function

| | | | |
|----------------------|--|-----------------------|---|
| Smart Service | <ul style="list-style-type: none"> • Association of one account with two POTS ports • L2 forwarding: 1G uplink, 2G downlink | Smart O&M | <ul style="list-style-type: none"> • Variable-length OMCI messages • Active/Passive rogue ONT detection and isolation • PPPoE/DHCP simulation testing • Call emulation, and circuit test and loop-line test |
| QoS | <ul style="list-style-type: none"> • Ethernet port rate limitation • 802.1p priority • SP/WRR/SP+WRR • Broadcast packet rate limitation • Flow mapping based on the VLAN ID, port ID, or/and 802.1p | Common O&M | <ul style="list-style-type: none"> • OMCI/Web UI • Dual-system software backup and rollback • 802.1ag Ethernet OAM • Optical link measurement and diagnosis • Loopback check |
| Security | <ul style="list-style-type: none"> • MAC address filtering | Multicast | <ul style="list-style-type: none"> • IGMP v2/v3 snooping • MLD v1/v2 snooping • Fast leave • VLAN tag translation, transparent transmission, and removal for downstream multicast packets • IGMP/MLD protocol packet rate limitation |
| Power Saving | <ul style="list-style-type: none"> • Indicator power saving • Power consumption reduction of idle components in power-saving state • COCv4 | | |